



## SAMURAI

# SUZUKI

### ARB DELUXE BULL BARS & WINCH BARS

<u>Year/Model</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
1986-95	Winch Bar	Recessed Indicators, Tow Points, Black	M6000, M8000 <sup>1</sup>	3424010

<sup>1</sup> Fitment of Warn M8000 winch may be fitted with minor modifications to bar.

### IPF LIGHTS & LIGHTING ACCESSORIES

<u>Year</u>	<u>Part No.</u>	<u>Recommended Lighting</u>
1986-95	3424010	800XSD, 900XS, 960S/R, 868CS, 968CS, J-01, 630RV

### SAFARI SNORKELS

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
N/A	N/A	N/A

### OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>	
Samurai Leaf Spring Models	Front	Stock/Light Load (0-55lbs)	Spring	1.25"	2	CS012FB <sup>1</sup>	
		Medium Load (55-125lbs)	Spring	1.50"	2	CS012FA <sup>1</sup>	
			Shock				OME025
	Rear	Heavy Load (125-200lbs)		Spring	1.25"	2	CS012FA <sup>1</sup>
				Shock			OME025
		Medium Load (0lbs to GVW)	Spring	1.50"	2	CS038R	
Installation	Leaf Spring Bushing Kit				4	OMESB19	
		U Bolts			6	OMEU60 <sup>4</sup>	
		U Bolts			2	OMEU62 <sup>4</sup>	
		Fitting Kit			1	FK06 <sup>5</sup>	
		Steering Damper			1	OMESD30	
	Optional	Trim Spacer					TP05
		Front Extra Leaf					D20XL <sup>6,4</sup>
		Rear Extra Leaf					D21XL <sup>6</sup>

<sup>1</sup> Important: Samurais used in extreme heavy off road conditions must have extra leaf D20XL added to front spring pack. U bolt OMEU61B is also required.

<sup>2</sup> Models without a front stabilizer bar require a firmer shock absorber than models with stabilizer bar. Correct selection will have a major effect on vehicle handling.

<sup>3</sup> OME013 fit all models except LJ80 and LJ80II. N43 fits all LJ80 and LJ80II models.

<sup>4</sup> Substitute two OMEU61B U bolts for OMEU60s when installing S1AXL/BXL Extra Leaf on front suspension.

<sup>5</sup> FK06 kit for stabilizer bar.

<sup>6</sup> Extra Leaf can be fitted for heavier constant load carrying ability.

### ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Model</u>	<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
	1984-98	Front	With leaf spring suspension	23.9 (0.94")	22	All	RD75
	1998-03	Front	Jimny model with 8 bolt RG	23.9 (0.94")	23	All	RD87
	1984 On	Rear	1.3 litre models only	27.4 (1.08")	26	All	RD88