

**TROOPER****ISUZU****ARB DELUXE BULL BARS & WINCH BARS**

<u>Year</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
1998-03	Winch Bar	Airbag Approved, Recessed Indicators, Urethane Buffers, Tow Points, Black	XD9000, M8000, M6000	3444070 ¹
	Winch Bar	Airbag Approved, Recessed Indicators, Urethane Buffers, Tow Points, Black	XD9000, M8000	3444060 ²
1992-98	Winch Bar	Recessed Indicators, Tow Points, Black	XD9000, M8000, M6000	3444050

¹ ARB Bar #3444070 measures 70.5" wide and suits models with "overfenders".² ARB bar #3444060 measures 68" wide and suits models with standard fender flares.**IPF LIGHTS & LIGHTING ACCESSORIES**

<u>Year</u>	<u>Type</u>	<u>Recommended Lighting</u>
1992-03	ALL	800XSD, 900XS, 900HID, 960 S/R, 868CS, 968CS, J-01

SAFARI SNORKELS

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
1992-97	3.1L Diesel Snorkel	SS200HF
	3.2L, V6 Snorkel	SS225HF

Refer to www.safari4x4.com.au for details.**OLD MAN EMU SUSPENSION PRODUCTS**

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
1992-02	Front	Stock/Light load	N/A	N/A	N/A	N/A ¹
			Shock		2	*N65/N26F
	Rear	Medium Load (0lbs to GVW)	Spring	1.0"	2	OME912 ²
			Shock		2	*N15/N15C
	Rear	Heavy Load (220lbs to GVW)	Spring	1.0"	2	OME919
			Shock		2	*N15/N15C
	Rear	Heavy Constant (440lbs to GVW)	Spring	.75"	2	OME929
			Shock		2	N15

¹ Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upper bump stop clearance and 2/3 lower bump stop clearance.² Coil must be installed with progressive rate to the top.

1982-3/92	Front	Stock/Light load	N/A	N/A	N/A	303004 ¹
			Shock		2	*N65/N26F
	Rear	Heavy Load (440lbs to GVW)	Spring	.75"	2	CS028R ³
			Shock		2	N88
	Installation	Leaf Spring Bushing Kit			2	OMESB90
	Optional	Rear Extra Leaf				RODXL ²

¹ Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upper bump stop clearance and 2/3 lower bump stop clearance.² Extra Leaf can be fitted for heavier constant load carrying ability.³ For Light Load applications, the 3rd leaf from the top of the spring pack can be removed for improved ride comfort.

* Firmer shock.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
1990 On	Front	Independent Suspension, IFS	28.4 (1.12")	17	ALL	RD94
1987-91	Rear	V6 Models Only	33.5 (1.32")	26	ALL	RD44
1993-97	Rear	All Models	33.5 (1.32")	26	ALL	RD44
1998-99	Rear	Non-LSD Models	38.1 (1.50")	23	ALL	RD85
2000 On	Rear	LSD Models ¹	38.1 (1.50")	23	ALL	NA ¹

¹ Third member may be swapped from pre-2000 non-LSD model for RD85 fitment.